

KOMBI 300



Categories: [Combined](#), [KOMBI](#)



COMBINED 5 OPERATIONS KOMBI 300

TECHNICAL DATA

Surface planer

Tables dimensions	mm 300x1500
Cutterblock diameter	mm 70
Rotation speed	rpm 5700
Knives dimensions (nr. 3 pcs)	mm 300x20x3
Max. table adjustment	mm 4

Thicknessing planner

Table dimensions	mm 300x660
Feed speed	m/1' 7
Min/max working height	mm 4-220

Mortiser

Table dimensions	mm 250x500
Longitudinal/transversal/vertical stroke	mm 205/95/90
Chuck diameter	mm 16

Panel saw

Table dimensions	mm 220x1000
Carriage dimensions	mm 1600x315
Saw blade/scoring blade speed	rpm 4500/7000
Saw blade diameter/hole	mm 250/30
Max. cutting height 45°/90°	mm 50/80
Max. distance between blade and fence	mm 500
Scoring blade diameter/hole	mm 90/22

Spindle moulder

Table dimensions	mm 220x1000
Rotation speed	rpm 2000/3100/4400/7000
Standard spindle diameter	mm 30/35/50
Vertical stroke	mm 115
Max. tool diameter under the table	mm 160
Tenoning depth	mm 55
Motor power	nr. 3 HP 3
Weight	kg 560

CE EQUIPMENT

- Nr. 1 clamp
- Spindle moulder fence

- Wescott chuck
- Table extension with swinging arm
- Nr. 3 knives
- Planer fence
- Saw fence
- Bridge safety hood on planer
- Nr. 3 dust aspiration hoods Ø 120 mm