

# TENO 1600-2200



Categories: [Combined](#), [TENO](#)



**SAW-SPINDLE COMBINED TENO 1600 - TENO 2200**

## TECHNICAL DATA:

	TENO 1600	TENO 2200
<b>Panel saw</b>		
Carriage dimensions	mm 1500x300	mm 2200x300
Table dimensions	mm 450x1250	mm 450x1250
Dimensions of the small table with fence fixed on the carriage	mm 320x500	mm 320x500
Saw blade diameter/hole	mm 315/30	mm 315/30
Cutting height 90°	mm 102	mm 102
Cutting height 45°	mm 72	mm 72
Width on parallel cutting	mm 850	mm 850
Saw blade speed	rpm 4000	rpm 4000
Saw motor power	HP 3	HP 3
<b>Spindle moulder</b>		
Available spindle diameters	30-35-40-50	30-35-40-50
Table opening diameter	mm 230	mm 230
Vertical stroke	mm 190	mm 190
Spindle speed	rpm 1500/3500/6000/8000	rpm 1500/3500/6000/8000
Spindle moulder motor power	HP 3	HP 3
Weight	kg 520	kg 580

## CE EQUIPMENT

- Widia blade  $\varnothing$  300 mm
- Spindle hood
- Blade protection
- Readout for tilting degrees
- Table fences
- Angular cutting device
- Eccentric clamp
- 4 dust extraction hoods (3 x  $\varnothing$  120 mm, 1 x  $\varnothing$  80 mm)
- Electronic system for motor braking
- Rounding safety hood
- Profiling safety hood CE type