

TENO 2600-3200



Categories: [Combined](#), [TENO](#)



SAW-SPINDLE COMBINED TENO 2600 - TENO 3200

TECHNICAL DATA

	TENO 2600	TENO 3200
Panel saw		
Carriage dimensions	mm 2700x350	mm 3200x350
Table dimensions	mm 650x1450	mm 650x1450
Squaring frame dimensions	mm 620x1200	mm 620x1200
Saw blade diameter/hole	mm 315/30	mm 315/30
Cutting height 90°	mm 102	mm 102
Cutting height 45°	mm 72	mm 72
Width on parallel cutting	mm 1080	mm 1080
Saw blade speed	rpm 4000	rpm 4000
Saw motor power	HP 4	HP 4
Spindle moulder		
Available spindle diameters (MK4 system)	30-35-40-50	30-35-40-50
Tilting spindle	90°/45°	90°/45°
Table opening diameter / depth	mm 260/60	mm 260/60
Vertical stroke	mm 175	mm 175
Spindle speed (2-speed motor)	rpm 3000/4000/5000 rpm 6000/8000/10000	rpm 3000/4000/5000 rpm 6000/8000/10000
Spindle moulder motor power (2-speed)	HP 4/5,5	HP 4/5,5
Weight	kg 700	kg 755

CE EQUIPMENT

- Widia blade \varnothing 300
- Interchangeable MK4 spindle
- Spindle hood \varnothing 250
- Blade protection
- Readout for tilting degrees
- Table fences
- Angular cutting device
- Eccentric clamp
- 4 dust extraction hoods (1 x \varnothing 120, 2 x \varnothing 100 mm, 1 x \varnothing 80 mm)
- Electronic system for motor braking
- Rounding safety hood
- Profiling safety hood CE type