

SBA PLUS



Categories: [AUTOMATIC](#), [Frame Clamps](#)

AUTOMATIC SINGLE BAR FRAME CLAMP SBA 30/17 PLUS - SBA 30/20 PLUS - SBA 35/20 PLUS - SBA 35/25 PLUS

TECHNICAL DATA

	SBA 30/17 PLUS	SBA 30/20 PLUS	SBA 35/20 PLUS	SBA 35/25 PLUS
Useful working length	mm 3000	mm 3000	mm 3500	mm 3500
Useful working width	mm 1700	mm 2000	mm 2000	mm 2500
Vertical pistons number	2	2	2	2
Vertical pistons diameter	mm 90	mm 90	mm 90	mm 90

Vertical pistons opening	mm 800	mm 1100	mm 1100	mm 1300
Thrust pressure for each vertical piston	kg 14000	kg 14000	kg 14000	kg 14000
Horizontal pistons number	2	2	2	2
Horizontal pistons diameter	mm 65	mm 65	mm 65	mm 65
Horizontal pistons opening	mm 1200	mm 1200	mm 1500	mm 1500
Thrust pressure for each horizontal piston	kg 4000	kg 4000	kg 6000	kg 6000
Motor power	HP 3	HP 3	HP 3	HP 3

CE EQUIPMENT

- Movable vertical beam
- Fixed vertical beam, 3 positions manually adjustable
- Fixed lateral fences
- Hydraulic handling of the lateral fences
- Hydraulic motor control unit with electro-valve unit
- Mobile panel for command in any position
- CE wiring