

KONTOUR 1200-1500 HYDRO



Categories: [KONTOUR](#), [Lathes](#)

LATHE WITH HYDRAULIC COPYING DEVICE KONTOUR 1200 HYDRO - KONTOUR 1500 HYDRO

TECHNICAL DATA

	KONTOUR 1200 HYDRO	KONTOUR 1500 HYDRO
Distance between centres	mm 1200	mm 1500
Height of centres over bed	mm 240	mm 240
Max. turning diameter	mm 460 (max. square mm 330)	mm 460 (max. square mm 330)
Max turning diameter with copying device	mm 200 (max. square mm 130)	mm 200 (max. square mm 130)

Useful copying stroke	mm 1100	mm 1400
Chuck speed	rpm 900/1500/2100/2800	rpm 900/1500/2100/2800
Motor power	HP 3	HP 3
Feed motor power	HP 0,5	HP 0,5
Weight	kg 450	kg 460

STANDARD EQUIPMENT

- Hydraulic copying device with motorized feed
- Copying tool
- Gouge support mm 350
- Chuck entrainer \varnothing 25 mm
- Rotating tailstock
- Service spanners

CE EQUIPMENT

- Hydraulic copying device with motorized feed
- Copying tool
- Gouge support mm 350
- Chuck entrainer \varnothing 25 mm
- Rotating tailstock
- Service spanners
- Self-braking motor
- Dust extraction hood \varnothing 80 mm