

# MC 500



Categories: [Multi-Rip Saw](#)

## MULTI-RIP SAW MC 500

### TECHNICAL DATA

Min./max. cutting width	mm 10/170
Min length of pieces	mm 740
Max passage	mm 940
Min./max. blade diameter	mm 405/505
Blade hole diameter	mm 80
Spindle diameter	mm 60

Blade revolutions	rpm 2800
Max external distance between the 2 blades	mm 455
Mat width	mm 500
Feed speed	m/min 7-30
Main motor power	HP 75
Feed motor power	HP 5,5
Lifting pressure rollers motor power	HP 1
External diameter of suction hood	mm 150x2
Working table dimension	mm 1000x2000
Working table height from the floor	mm 810
Weight	kg 4300

## STANDARD EQUIPMENT

- Blade sleeve complete with spacer rings as follow: nr.3 mm 50 / nr.7 mm 20 / nr.6 mm 15 / nr.6 mm 10 / nr.2 mm 8 / nr.7 mm 5 / nr.7 mm 1 / nr.7 mm 0,5 / nr.7 mm 0,3
- Automatic lubrication

## CE EQUIPMENT

- Blade sleeve complete with spacer rings as follow: nr.3 mm 50 / nr.7 mm 20 / nr.6 mm 15 / nr.6 mm 10 / nr.2 mm 8 / nr.7 mm 5 / nr.7 mm 1 / nr.7 mm 0,5 / nr.7 mm 0,3
- Automatic lubrication
- CE wiring